




SCAN GLORY: NORSEMAN I SERIES

1500HP - SCR, 7500PSI, Walking Capable



HOISTING, ROTATING & PIPE-HANDLING EQUIPMENT

Drawworks: OWI

Rotary Table: 27.5"

Traveling Block: 500 Ton

Top Drive: TDS 11

Iron Roughneck: ST-80

Hydraulic Catwalk: Canrig

Static Hook Load: 1,000,000#

MAST & SUBSTRUCTURE

Mast Design: Spindletop

Mast Height: 142'

Racking Capacity: 25,000' of 5" Drill Pipe

Floor Height: 26' / Rotary Beam Clearance: 22-3"

TRANSPORT

Estimated Loads: ?

POWER PACKAGE

Engines: Three(3) Caterpillar 3512C Diesel Engines

Generators: Three (3) 1365 Kw Kato Generators

SCR System: IEC

BOP EQUIPMENT

Annular: 13-5/8" 5K

Double Ram: 13-5/8" 5K

Accumulator: 6 Station

Choke Manifold: 5K

Mud/Gas Separator: Shop Built



MUD SYSTEM

Mud Pumps: Two (2) F1600 with 7500 psi Fluid Ends

Liquid Mud Tanks: Two (2) with 1000 bbl Total Capacity

Trip Tank: 80 bbl

Shale Shakers: Three (3) Swaco Mongoose

Reserve Pit	Laydown End
150'	150'
Power End	Turn Around End
Mouse hole center 6'-3" from well center	

TUBULARS

Drill Pipe: 5" Drill Pipe as Needed

Drill Collars: As needed per Customer's Well Program

PAD DRILLING (MULTI DIRECTIONAL)

Walking System/Type: Spindletop (Stomper Type)

Pad Walking Distance 0' to 100'