




SCAN DENALI: NORSEMAN II SERIES

2000HP - AC, 7500PSI, Walking Capable



HOISTING, ROTATING & PIPE-HANDLING EQUIPMENT

Drawworks: OWI 2000 AC

Rotary Table: 27.5"

Traveling Block: 500 Ton

Top Drive: GDS TDS11 Hi-Tork AC 500 Ton

Iron Roughneck: Forum FR-120

Hydraulic Catwalk: Hydraulic

Static Hook Load: 1,000,000#

MAST & SUBSTRUCTURE

Mast Design: Spindletop

Mast Height: 142'

Racking Capacity: 29,500' of 5 1/2" Drill Pipe Floor

Height: 28' / Rotary Beam Clearance: 26.5'

TRANSPORT

Estimated Loads: 55 loads (without drill pipe)

POWER PACKAGE

Engines: Four (4) Caterpillar 3512C Diesel Engines

Generators: Four (4) 1365 Kw Kato Generators

AC System: Current Power, equipped with CAT DGB

Gas System

BOP EQUIPMENT

Annular: 13-5/8" 5K

Double Ram: 13-5/8" 10K

Accumulator: 6 Station

Choke Manifold: 10K

Mud/Gas Separator: Shop Builf

Single Ram: 13-5/8" 10K



MUD SYSTEM

Mud Pumps: Three (3) F1600 with 7500 psi Fluid Ends

Liquid Mud Tanks: Two (2) with 1000 bbl

Total Capacity Trip Tank: 100bbl

Shale Shakers: Three (3) Derrick Hyperpool

Location Plat

TUBULARS

Drill Pipe: 5" Drill Pipe as Needed

Drill Collars: As needed per Customer's Well Program

PAD DRILLING (MULTI DIRECTIONAL)

Walking System/Type: Spindletop (Stomper Type)

Pad Walking Distance 0' to 100'