



# SCAN PRODUCER: NORSEMAN I SERIES

1500HP - SCR, 7500PSI, Walking Capable



## HOISTING, ROTATING & PIPE-HANDLING EQUIPMENT

Drawworks: Oilwell Model 840E  
 Rotary Table: 27.5"  
 Traveling Block: 500 Ton  
 Top Drive: 500 Ton AC CANRIG  
 Iron Roughneck: Forum FH-80  
 Hydraulic Catwalk: NOV  
 Static Hook Load: 750,000#

## MAST & SUBSTRUCTURE

Mast Design: Pyramid Derrick & Equipment Corp.  
 Mast Height: 142'  
 Racking Capacity: 22,000' of 5" Drill Pipe  
 Floor Height: 27' / Rotary Beam Clearance: 22'-6"

## TRANSPORT

Estimated Loads: 51  
 without drill pipe

## POWER PACKAGE

Engines: Three(3) Caterpillar 3512C Diesel Engines Dual  
 Generators: Three(3) 1365 Kw Kato  
 SCR System: M&I Electric Model 1612


## BOP EQUIPMENT

Annular: 13-5/8" 5K  
 Single Ram: 13-5/8" 10K  
 Double Ram: 13-5/8" 10K  
 Accumulator: Koomey T20120-3S  
 Choke Manifold: 10K  
 Mud/Gas Separator: Shop Built

## MUD SYSTEM

Mud Pumps: Three (3) F1600 with 7500 psi Fluid Ends  
 Liquid Mud Tanks: Two (2) with 1000 bbl Total Capacity  
 Trip Tank: 80 bbl Total Capacity  
 Shale Shakers: One (1) Derrick Dual FLC 503  
 Two (2) Derrick Single FLC 503

Location Plat



## TUBULARS

Drill Pipe: 5" Drill Pipe as Needed  
 Drill Collars: As needed per Customer's Well Program

## PAD DRILLING (MULTI DIRECTIONAL)

Walking System/Type: Veristic Mfg (Stomper Type)  
 Pad Walking Distance :0'-100'